

## >> ABC X-CPU-6 m57 – the modular CPU solution for the Simatic S5-Racks

The ABC X-CPU-6 m57 is a central module for use in the automation systems of the SIMATIC S5 by Siemens. The module is programmable in STEP5, STEP7, PCS7 and TIA by Siemens and is suitable for restructuring and upgrading projects.

4 Gigabit CPUs, 3 fieldbus masters and the unique opportunity to work with S5 and S7 programs simultaneously, give a new dimension to the topic of retrofit SIMATIC S5 systems.



### **ABC-RS7 416 CPU-software**

### **ABC-RS7 416-945 CPU-software**

### **ABC-RS7 416-948 CPU-software**

### **ABC-RS5 945 CPU-software**

### **ABC-RS5 948 CPU-software**

- Intel® Atom™ Processor E3845 1.91 GHz, L2 Cache 2MB
- 4x integrated 10/100/1000 Mbps Ethernet Interfaces
- 2GB memory on board
- Remanent data storage without using the backup battery of the S5-rack
- SD card for the system, program and data
- 3 serial interfaces (1x TTY, 2x RS232)
- LED diagnostics display
  
- For use in SIMATIC racks of 115U, 135/155U and 150U/S/K by Siemens
- Command compliant to S7-CPU 416 also in Mixed Mode as 416-945/948
- Quantity structure/Performance equates to S7-CPU417
- Command compliant to S5-CPU 945/948
- Supports multiprocessor communication with up to 3x S5-CPU948 and 1x S7-CPU416
- Programmable in STEP5, STEP7, PCS7 and TIA
- Complete TCP/IP connection for linking of homogeneous and heterogeneous system components integrated
- High Performance (average 10ns/operation)
- Modbus TCP-Server
- Up to three fieldbus masters Profibus, Profinet, EtherCAT

#### **ABC IT GmbH**

Virchowstraße 19/19a • 90409 Nuremberg /Germany  
Fon +49-(0)911-394 800 0 • Fax +49-(0)911-394 800 99  
<http://www.abcit.eu> • E-Mail: mail@abcit.eu

## Technical data hardware:

<b>Processor</b>	Intel® Atom™ Processor E3845
<b>Electrical Data</b>	+5Vdc: 4.85V...5.24V
<b>Operating conditions</b> <ul style="list-style-type: none"> <li>▪ Operating temperature</li> <li>▪ Storage temperature</li> <li>▪ Relative humidity</li> <li>▪ Vibration and shock resistance</li> <li>▪ EMC / burst / ESD</li> </ul>	0°C ... +60°C -40°C...85°C During operations: max. 90 % without condensation 2g/10..500Hz, 20g/10ms acc. IEC1000-4-2 (ESD) acc. IEC1000-4-4 (burst) Emissions acc. 55022, Part B
<b>LEDs</b>	4 LEDs as status and fault indicators
<b>Dimensions</b>	Double Eurocard, height 8 HU
<b>Interfaces</b> Serial  Ethernet	1 x AS 511 (TTY) with DSUB 15 2 x RS232 with DSUB 9 4 x 10/100/1000 Mbps.
<b>Memory extension</b>	2 GB DDR2-667 MHz 8 GB SD Memory Card 64 MB remanent

## Technical data software RS5:

<b>Processing times</b>	Bit operations	10 ns
	Word operations	10 ns
	Fixed point arithmetics	10 ns
	Floating-point arithmetics	10 ns

## Technical data Software RS7:

<b>Processing times</b>	Bit operations	10 ns
	Word operations	10 ns
	Fixed point arithmetics	10 ns
	Floating-point arithmetics	10 ns
<b>Timers / Counters</b>	S7 timers 2048	S7 counters 2048
<b>Data range and remanence</b> Markers Process image  Blocks FBs max. FCs max. Data blocks max. Alarms Load memory Work memory Communication jobs	16 KByte from MB 0 to MB 16383 16 KByte In/16 KByte Out From EB 0 to EB16383/AB 0 to AB16383 max. 64 KByte 65535 65535 65534 9 wake-up alarms 20 Mbyte 16 Mbyte 10000	